

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)


PCT

(10) International Publication Number  
**WO 2004/030147 A1**

- (51) International Patent Classification?: **H01Q 3/26**
- (21) International Application Number: **PCT/FI2002/000765**
- (22) International Filing Date: **24 September 2002 (24.09.2002)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (71) Applicant (for all designated States except US): **NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **YLITALO, Juha [FI/FI]; Kylmäniementie 19, FIN-90540 Oulu (FI).**
- (74) Agent: **KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).**
- (81) Designated States (national): **AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (81) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**

[Continued on next page]

(54) Title: **COMPENSATING FOR RADIATION PATTERN IN RADIO SYSTEM, AND RADIO SYSTEM**



(57) Abstract: The invention relates to compensation of a radiation pattern in a radio system. The solution comprises forming a primary radiation pattern by weighting signals of antenna branches with primary weights. The primary radiation pattern is compensated with a compensating radiation pattern after one or more antenna branches have been disconnected. The solution enables operation of the radio system without interruptions in certain fault situations of the base station.

WO 2004/030147 A1